## 2N2920 2N2920A

# SILICON DUAL NPN TRANSISTORS




www.centralsemi.com

# **DESCRIPTION:**

The CENTRAL SEMICONDUCTOR 2N2920 and 2N2920A are dual silicon NPN transistors manufactured by the epitaxial planar process utilizing two individual chips mounted in a hermetically sealed metal case designed for differential amplifier applications.





MAXIMUM RATINGS: (T <sub>A</sub> =25°C)	SYMBOL		UNITS
Collector-Base Voltage	$V_{CBO}$	60	V
Collector-Emitter Voltage	$V_{CEO}$	60	V
Emitter-Base Voltage	$V_{EBO}$	6.0	V
Continuous Collector Current	$I_{\mathbb{C}}$	30	mA
Power Dissipation (One Die)	$P_{D}$	300	mW
Power Dissipation (Both Dice)	$P_{D}$	500	mW
Power Dissipation (One Die, T <sub>C</sub> =25°C)	$P_{D}$	750	mW
Power Dissipation (Both Dice, T <sub>C</sub> =25°C)	$P_{D}$	1.5	W
Operating and Storage Junction Temperature	T <sub>J</sub> , T <sub>stg</sub>	-65 to +200	°C
ELECTRICAL CHARACTERISTICS PER TRA	NSISTOR: (T <sub>A</sub> =25°C	unless otherwise noted)	
SYMBOL TEST CONDITIONS	MIN	MAX	UNITS

Operating and	1 Storage Junction Temperature	'J, 'stg	-03 10 +200	C
ELECTRICAL CHARACTERISTICS PER TRANSISTOR: (T <sub>A</sub> =25°C unless otherwise noted)				
SYMBOL	TEST CONDITIONS	MIN	<b>MAX</b> 2.0	UNITS
ICBO	$V_{CB}=45V$			nA
ICEO	V <sub>CE</sub> =5.0V		2.0	nA
I <sub>EBO</sub>	V <sub>EB</sub> =5.0V		2.0	nA
BV <sub>CBO</sub>	I <sub>C</sub> =10μA	60		V
BVCEO	I <sub>C</sub> =10mA	60		V
BVEBO	I <sub>E</sub> =10μA	6.0		V
V <sub>CE(SAT)</sub>	$I_C$ =1.0mA, $I_B$ =100 $\mu$ A		0.35	V
V <sub>BE(ON)</sub>	$V_{CE}$ =5.0V, $I_{C}$ =100 $\mu$ A		0.70	V
hFE	$V_{CE}$ =5.0V, $I_{C}$ =10 $\mu$ A	150	600	
h <sub>FE</sub>	$V_{CE}$ =5.0V, $I_{C}$ =10 $\mu$ A, $T_{A}$ =-55 $^{\circ}$ C	40		
hFE	$V_{CE}$ =5.0V, $I_{C}$ =100 $\mu$ A	225		
hFE	$V_{CE}$ =5.0V, $I_{C}$ =1.0mA	300		
f <sub>T</sub>	$V_{CE}$ =5.0V, $I_{C}$ =500 $\mu$ A, f=20MHz	60		MHz
C <sub>ob</sub>	$V_{CB}$ =5.0V, $I_{E}$ =0, $f$ =140kHz		6.0	pF
NF	$V_{\text{CE}}$ =5.0V, $I_{\text{C}}$ =10 $\mu$ A, $R_{\text{S}}$ =10 $k\Omega$ ,			
	f=1.0kHz, BW=200Hz		3.0	dB

R1 (4-April 2014)

# 2N2920 2N2920A






# MATCHING CHARACTERISTICS: (T<sub>A</sub>=25°C unless otherwise noted)

		2N2	920	2N29	20A	
SYMBOL	TEST CONDITIONS	MIN	MAX	MIN	MAX	UNITS
h <sub>FE1</sub> /h <sub>FE2</sub> *	$V_{CE}=5.0V, I_{C}=100\mu A$	0.9	1.0	0.9	1.0	
$ V_{BE1}-V_{BE2} $	$V_{CE}$ =5.0V, $I_{C}$ =10 $\mu$ A	-	5.0	-	2.0	mV
$ V_{BE1}-V_{BE2} $	$V_{CE}$ =5.0V, $I_{C}$ =100 $\mu$ A	-	3.0	-	1.5	mV
$\Delta(V_{BE1}-V_{BE2})$	$V_{CE}$ =5.0V, $I_{C}$ =100 $\mu$ A, $T_{A}$ =-55 $^{\circ}$ C to +25 $^{\circ}$ C	-	8.0	-	-	mV
$\Delta(V_{BE1}-V_{BE2})$	$V_{CE}$ =5.0V, $I_{C}$ =100 $\mu$ A, $T_{A}$ =+25°C to +125°C	-	1.0	-	-	mV

<sup>\*</sup>The lowest reading is taken as h<sub>FE1</sub>.


## **TO-78 CASE - MECHANICAL OUTLINE**

R1



DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A (DIA)	0.335	0.370	8.51	9.40
B (DIA)	0.305	0.335	7.75	8.51
С	0.150	0.185	3.81	4.70
D	-	0.040	-	1.02
E	0.500	•	12.70	-
F (DIA)	0.016	0.021	0.41	0.53
G	0.2	200	5.	08
Н	0.100		2.	54
J	0.028	0.034	0.71	0.86
K	0.029	0.045	0.74	1.14
TO 70 (DEL) DA)				

TO-78 (REV: R1)



MARKING: FULL PART NUMBER


R1 (4-April 2014)


## 2N2920 2N2920A


# SILICON DUAL NPN TRANSISTORS





# TYPICAL ELECTRICAL CHARACTERISTICS











R1 (4-April 2014)

### **OUTSTANDING SUPPORT AND SUPERIOR SERVICES**



#### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

#### **DESIGNER SUPPORT/SERVICES**

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- Custom product and package development

#### REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

#### **CONTACT US**

### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

**Worldwide Distributors:** 

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <a href="https://www.centralsemi.com/terms">www.centralsemi.com/terms</a>

www.centralsemi.com (001)



# Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

Summary: All transistors manufactured in the TO-78 package are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement
CEN876	N/A
CEN894	N/A
CEN895	N/A
CEN896	N/A
CEN911	N/A
CEN947	N/A
CEN955 W/DATA	N/A
MD2219A	N/A
MD2369	N/A
MD2369A	N/A
MD2369B	N/A
MD2905	N/A
MD2905A	N/A
MD5179	N/A
MD7000	N/A
MD7001	N/A
MD7003	N/A
MD7003A	N/A
MD7003B	N/A
MD8002	N/A
MD8003	N/A
MD918	N/A
MD918A	N/A
MD918B	N/A
MD984	N/A
2N2060	N/A
2N2060A	N/A
2N2060M	N/A
2N2223	N/A
2N2223A	N/A
2N2453	N/A
2N2453A	N/A
2N2480	N/A
2N2480A	N/A
2N2639	N/A
2N2640	N/A
2N2641	N/A
2N2642	N/A
*** CONTINUED ***	

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002



# Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

\*\*\* CONTINUED FROM PRIOR PAGE \*\*\*

C . ID . N I	<b>D</b> 1
Central Part Number	Replacement
2N2643	N/A
2N2644	N/A
2N2652	N/A
2N2652A	N/A
2N2720	N/A
2N2721	N/A
2N2722	N/A
2N2903	N/A
2N2903A	N/A
2N2913	N/A
2N2914	N/A
2N2915	N/A
2N2915A	N/A
2N2916	N/A
2N2916A	N/A
2N2917	N/A
2N2918	N/A
2N2919	N/A
2N2919A	N/A
2N2920	N/A
2N2920A	N/A
2N3726	N/A
2N3727	N/A
2N3806	N/A
2N3807	N/A
2N3808	N/A
2N3809	N/A
2N3810	N/A
2N3810A	N/A
2N3811	N/A
2N3811A	N/A
2N4015	N/A
2N4016	N/A
2N4854	N/A
2N4937	N/A
2N4938	N/A
2N4939	N/A
2N5793	N/A
2N5794	N/A
2N5796	N/A
2N5912	N/A
2N6502	N/A

\*\*\* CONTINUED \*\*\*

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002



# Product End of Life Notification

PDN ID:	PDN01061
Notification Date:	1/17/17
Last Buy Date:	7/17/17
Last Shipment Date	1/17/18

\*\*\* CONTINUED FROM PRIOR PAGE \*\*\*

Central Part Number	Replacement
Central would be happy to assist yo	ou by providing additional information or technical data to help locate an alternate source if we
have no replacement available. Plea	ase email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor: 2N2920