



Amidon™



[Distribution Lines Carried](#) [Blog](#) [Info](#) [Policy](#) [Shipping](#) [Contact](#) [Links](#)

[Specifications](#) [CART](#) [MY ACCOUNT](#)

[Ferrites](#) [Iron Powder Toroids](#) [Books](#) [Kits](#) [Mounts and Bobbins](#) [Tunable Inductors](#)

[Wire, Tape, PTFE Tubing](#) [Connectors](#) [Cable & Harness Assembly](#)

[Home](#) [Ferrites](#) [Ferrite Toroids](#) [FT-63A-61](#)

[Home](#) [Ferrites](#) [Ferrite Toroids](#) [61 Material Ferrite Toroids](#) [FT-63A-61](#)



FT-63A-61



Product Description

61 Material and is designed for inductive applications up to 25 MHz and also suppresses noise frequencies from 200 MHz to 1000 MHz

*All AL values are $\pm 25\%$ *

Inner Diameter: 0.378

Outer Diameter: 0.630

Height: 0.250

AL Value: 80

Other Details

Inner Diameter:

0.378

Outer Diameter:

0.630

Height:

0.250

AL Value:

80

Product Reviews

WRITE REVIEW

This product hasn't received any reviews yet. Be the first to review this product!

Find Similar Products by Category

- Ferrites
- Ferrite Toroids

- Ferrites
- Ferrite Toroids
- 61 Material Ferrite Toroids

Related Products