Ceramic Trimmer Capacitors

multicomp

Ultra-Miniature





Specifications:

Maximum working voltage Dielectric strength Insulation resistance Maximum working temperature : 200 V dc
: 500 V dc at maximum capacitance
: 10,000 MΩ at 250 V dc at maximum capacitance

: 10,000 MΩ at 250 V dc at maximum capacitand : 85° C

Specification Table

Colour	Maximum Capacitance (pF)	Minimum Capacitance (pF)	Q (at maximum C) F = 10 MHz	Temperature Co-efficient	Part Number
Red	6	1.5	300 minutes	NPO ±250	CV05 A0601
Nil	12.5	2.8		N600 ±250	CV05 C1201
Blue	20	3.5		N750 ±300	CV05 D2001
Yellow	30	5		N1500 ±300	CV05 E3001
Green	50	5.5		N1500 ±500	CV05 E5001

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Famell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheets previously for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.



www.element14.com www.farnell.com www.newark.com