





Parts	Material	Plating (Micro-inch)
Barrel	Brass	Gold 5 Over Nickel 50 Over Copper 50
Contact Pin	Phosphor Bronze	Gold 20 Over Nickel 50 Over Copper 50
Insulator	Teflon	
Body	Brass	Gold 5 Over Nickel 50 Over Copper 50
Coupling Nut	Brass	Gold 5 Over Nickel 50 Over Copper 50

Weight: 1.46 g

Suitable Cables: Semi-rigid.085

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



## CABLE ASSEMBLY INSTRUCTION SMC3300-0085 JYE BAO CO., LTD. Ε Α CONTACT PIN BODY \*TOOLS AND FIXTURES ARE REFERENCE ON PAGE 306 OF JYEBAO'S 2005 CATALOG. ASSEMBLY INSTRUCTION DIAGRAM [.146] Step 1: STRIP AS SHOWN. Е Step 2: PUT 0.2 MM GAGE IN PLACE, INSERT CABLE'S CENTER CONDUCTOR INTO CENTER PIN " E " AND SOLDER IN " Y ". GAGE 0.2MM ST-009 Step 3: INSERT PREPARED CABLE INTO SOLDER-ING FIXTURE "ST-008". USE INSERT TOOL "ST-009" AND LOCATOR TOOL "ST-011" TO FIX THE CONNECTOR . SOLDER IN " $\mathsf{X}$ " . ST-011 ST-008

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.