


REV.	DATE	DESCRIPTION	
C	04/31/03	UPDATE DRAWING FORMAT	







RECOMMENDED CABLE STRIPPING DIMENSIONS

					UNI	
8					INC	
7						
6						
5	GASKET	SILICONE	RED	1		
4	RETAINER RING	BER. COPPER	NATURAL	1		
3	CONTACT PIN	BRASS	GOLD	1		
2	INSULATOR	TEFLON	NATURAL	1		
1	SHELL/BODY	BRASS	GOLD	1	1.	
	DESCRIPTION	MATERIAL	FINISH	QTY		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE
IN MILLIMETERS, DIMENSIONS IN [] ARE IN
INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR MILLIMETERS ARE:

0.5 - 8mm ± 0.20mm
8 - 30mm ± 0.40mm
30 - 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR INCHES ARE:

0.20 - 315 = ± 0.007"

.020 - .315 = ± 0.007" .315 - 1.180 = ± 0.015" 1.180 - 4.724 = ± 0.020"

RE Y.	APPROVALS	DATE	
'.	DRAWN G.R.S.	04/31/03	
	CHECKED		
	ISSUED		
	SHEET 1 OF 1		
	CAD FILE   C:/132/132102.DWG		

## **Amphenol Connex**

PART DESCRIPTION

SMA SEMI-RIGID PLUG (FOR .141" SEMI-RIGID CABLE)

PART NO.

132102

DWG. NO. 132102.DWG

REV. C SIZE A SCALE NA

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 $\frac{\text{Amphenol}}{\frac{132102}{}}$